

A Review on License Plate Recognition with Experiments for Malaysia Case Study

¹Nuzulha Khilwani Ibrahim, ¹Emaliana Kasmuri, ¹Norazira A. Jalil,
¹Mohd Adili Norasikin, ¹Sazilah Salam and ²Mohamad Riduwan M.D. Nawawi

¹Faculty of Information and Communication Technology,
Universiti Teknikal Malaysia Melaka (UTeM), Hang Tuah Jaya, 76100 Melaka, Malaysia

²Faculty of Electrical Engineering, Universiti Teknikal Malaysia Melaka (UteM),
Hang Tuah Jaya, 76100 Melaka, Malaysia

Abstract: Most vehicle license plate recognition use neural network techniques to enhance its computing capability. The image of the vehicle license plate is captured and processed to produce a textual output for further processing. This paper reviews image processing and neural network techniques applied at different stages which are preprocessing, filtering, feature extraction, segmentation and recognition in such way to remove the noise of the image, to enhance the image quality and to expedite the computing process by converting the characters in the image into respective text. An exemplar experiment has been done in MATLAB to show the basic process of the image processing especially for license plate in Malaysia case study. An algorithm is adapted into the solution for parking management system. The solution then is implemented as proof of concept to the algorithm.

Key words: Image processing • Preprocessing • Filtering • Feature extraction • Segmentation • Recognition • Experiment

INTRODUCTION

The advanced of computer application processed more than textual data solving everyday problems. Inputs from optical device are used in domain application such as medical, security, monitoring and control and engineering. Ability for computer to process image and translate it into something meaningful has become more popular. Therefore, the technology of image processing has adopted in managing vehicle parking system, vehicle access to restricted area, traffic monitoring system and highway electronic toll collection. For this purpose, the computer needs to capture the vehicle licence plate number and process it in the computer.

A camera captures the image of vehicle license plate. The image then feed into the computer for further processing. The output of from the process is the vehicle license plate number in textual form. For a parking system, the output is used for car identification, parking payment and authorization to access into the parking space.

This paper reviews the processing of vehicle license plate that uses image processing and neural network technique.

The framework for this research is adapted from previous studies [1-4] as shown in Figure 1 which includes 5 stages: (a) pre-processing, (b) filtering, (c) feature extraction, (d) segmentation and (e) character recognition. The final output of the sample experiment is to recognize the alphanumeric characters on the license plate. The structure of this paper is organized by the stages of the process.

Preprocessing: Digital image preprocessing is an initial step to image processing improving the data image quality for more suitable for visual perception or computational processing. Preprocessing remove unwanted data and enhance the image by removing background noise, normalizing the intensity of individual image particles, image deblur and remove image reflections. Preprocessing for car license plate number uses three common subprocesses, which are geometric operation, grayscaleing process and binarization process.

Corresponding Author: Nuzulha Khilwani Ibrahim, Faculty of Information and Communication Technology,
Universiti Teknikal Malaysia Melaka (UTeM), Hang Tuah Jaya, 76100 Melaka, Malaysia.




Fig. 1: Research framework

Many neural network techniques have been applied to these preprocessing techniques mainly to produce better image and to increase the speed of convergence of an image.

The research is funded for Malaysian Technical University Network - Centre of Excellence (MTUN CoE) program with grant no MTUN/2012/ UTem-FTMK/11 M00019.

Geometric Operation: Geometric operation is a process to locate the car license plate. The purpose of this operation is to localize the car plate for faster character identification over a small region.

An improved Back Propagation network is used to overcome the weakness of convergence speed in [1]. Genetic algorithm and momentum term is introduced to the current network to increase the speed of convergence rate. The current BP network learning process is said to be easily produce error if initial weights is not set properly [1] and it is difficult to determine the number of hidden layer and hidden nodes. The improved network using BP momentum increase the speed and the accuracy to localize the car license place location. A grayscale image extracts the edge of the license plate using sobel operator [1].

Malviya and Bhirud in [2] uses iterative thresholding operation to identify license plate of a vehicle. Objects with geometric characteristics are labelled and selected. The process takes into account aspect ratio, total pixel per object, height, width and the presence of characters in the region.

For this, we propose the following algorithm, where the pseudo-code can be simplified as the following:

- To get the scale of the image for x-axis and y-axis.
- To assign the new value of horizontal and vertical axis based on the scale of the x-axis and y-axis.
- To get the grayscale thresholding value of the image.

The input of the experiment is shown as Figure 2 while the example output can be viewed as Figure 3.

The output from the extraction process will be used in the next stage which is grayscale process.



Fig. 2: Input data for License Plate Image Processing



Fig. 3: Image output after geometric operation process

Grayscale Process: Grayscale is a process to produce a gray scale image from a multicolor image. In this process, the threshold of an image is calculated. If it is less than the threshold, the image data is recalculated to get the correct grayscale value. The purpose of thresholding is to separate the object of interest from the background. Thresholding is important to provide sufficient contrast for the image so that different level of intensity between object and the background can be differentiated for later computational processing. Different intensity determines the value of the threshold.

Grayscale process improves the quality of the image for later computational processing. Other preprocessing techniques to improve the quality of the image including image deblurring, image enhancement, image fusion and image reconstruction.

Image fusion is a process to enhance the image with multiple combinations of images [2-3]. This process is suitable to identify the car license registration number from a moving car. The technique integrates multi resolution image and produce a composite image using inverse multiresolution transform [3]. A template of image from a grayscale is shifted to vertical and horizontal direction. The contrast frequency is calculated for each position in the template and creates a new image using thresholding procedure. Any color below the threshold is

set to black (zero) and above threshold is set to white (one). The value determines the gray level resulting black and white image.

A trained feedforward neural network (FFN) with Block Recursive LS algorithm is used to process car license plate [4]. The approach is to improve the convergence rate and stabilize the robustness of the solution. The location of the car license plate is extracted using Discrete Fourier Transform (DFT). DFT identifies maximum value of horizontal and vertical edges. Prior to that tone equalization and contrast reduction is used to improve the image. These techniques are preferred because it is more robust and suitable compared to edge enhancement.

For this, we propose the following algorithm, where the pseudo-code can be simplified as the following:

- To convert into grayscale image

The pseudo-code can be translated in MATLAB such as following:

- `TestImg1 =rgb2gray (TestImg1);`

Binarization Process: Binarization is a process of converting grayscale image into black and white image or “0” and “1”. Previously, the gray scale image consists of different level of gray values; from 0 to 255. To improve the quality and extract some information from the image, the image needs to be process a few times and thus make the binary image more useful. Gray threshold value of an image is required in the binarization process as it is important to determine whether the pixels that having gray values will be converted to black or white.

For this, we propose the following algorithm, where the pseudo-code can be simplified as the following:

- To convert into black and white image

The pseudo-code can be translated in MATLAB such as following:

- `ImgBW =im2bw(TestImg1 ,threshold`

The example output can be viewed as Figure 4.

The output from the extraction process will be used in the next stage of the processing in this framework which is filtering.



Fig. 4: Image output after binarization process

Filtering: To enhance the quality of processing image, filtering is required to solve contrast enhancement, noise suppression, blurry issue and data reduction. It is reported that most of preprocessing activities conducted in image restoration apply Neural Network approach [5].

Rectangles’ filtering implemented on the real plate number involves convolution matrix, binarization filter with vertical and horizontal projection able to enhance the image quality and eliminates unwanted pieces on the plate. It is also recognize the number of rows and symbols in the plate number [6].

In [7], a simple filter is designed by implementing intensity variance and edge density to overcome illumination issue, distance changed and complex background. It is proposed that this approach convenient for real-time application.

The quality and selection of parameters on the camera extremely contributes the desired preprocessing image quality [8].

The example output can be viewed as Figure 5. The output from the extraction process will be used in the next stage which is image segmentation.

Feature Extraction: Features extraction is the part of measuring those relevant features to be used in recognition process. Selection of the right features is important in order to obtain best results in license plate recognition study. Colour features are very good potential for object detection. However the parameter such as colour of car, illumination condition and the quality of imaging system has been limited its practice [9]. According to [10], colour features have been studied by [11] and [12] but from the study, this feature not robust enough to various environments. However, there are many types of features that can aid license plate recognition such as aspect ratio, texture, edge density and size of region [10]. In order to achieve better detection rate in license plate recognition, researchers in [10] and [13] had suggested a combination of features. For instance, a promising result for combination of colour and edge has been reported in [14]. Moreover, [9] has reported that the



Fig. 5: Image output after filtering process

use of simple geometrical features such as shape, aspect ratio and size are enough to find genuine license plate. However the researchers face problem such as clutter parts in the image and overcome it with edge density. Edge features of the car image are very important and edge density can be used to successfully detect a number plate location due to the characteristics of the number plate [9]. The edge density features had been used in [9, 10, 13] because the density of vertical edges at the license plate area is considerably higher than its neighbourhood. In addition, this feature is more reliable and able to reduce processing time. Little computational time is one of important element in recognition especially in real-time detection. However, there is always trade-off between the number of features used in the system and the computational time [9, 13].

For this, we propose the following algorithm, where the pseudo-code can be simplified as the following:

- To compare the vertical and horizontal histogram in getting the required features.
- To extract the meaningful image based on the features selected

Then, the horizontal and vertical histograms are combined to get the matching region of a license plate is kept as candidate region or also known as meaningful image. The example output can be viewed as Figure 6 and Figure 7.

The output from the extraction process will be used in the next stage which is image segmentation.

Image Segmentation: One of the most popular topics in image processing study is image segmentation. The segmentation process becomes important to the processing of the image to find the meaningful information where it comes from the meaningful regions which represent higher level of data. The analysis of image requires large amount of low level of data which is in pixel to be extracted into meaningful information.




Fig. 6: Image output after feature selection process



Fig. 7: Image output after feature extraction process

Higher-level object properties can be incorporated into segmentation process, after completing certain preliminary segmentation process. Examples of higher-level properties are as follow:

- Shape, or
- Colour features

Then, it comes to the goal of segmentation which is to find regions that represent meaningful parts of objects. In segmentation, the image will be divided into regions based on the interest of the study.

Image segmentation methods will look for objects that either have some measure of homogeneity (within themselves), or contrast (with the objects on their border). Most image segmentation algorithms can be divided as the following:

- Modifications,
- Extensions, or
- Combination of these 2 basic concepts

Classically, Umbaugh in [15] divide image segmentation techniques into three (3) which are:

- Region growing and shrinking: subset of clustering
- Clustering methods.
- Boundary detection: extensions of the edge detection techniques.

At the same point, Haralick and Shapiro [16] categorized image segmentation techniques into six (6) which are:

- Measurement space guided spatial clustering.
- Single linkage region growing schemes.
- Hybrid linkage region growing schemes.
- Centroid linkage region growing schemes.
- Spatial clustering schemes.
- Split and merge schemes.

Clustering is one of the segmentation technique as Haralick and Shapiro [16] differentiated clustering and segmentation such as follow:

- In clustering: the grouping is done in measurement space.
- In segmentation: the grouping is done in the spatial domain of the image.

Clustering techniques can be used to any domain, eg: any N-dimensional color or feature space, including spatial domain's coordinates. This technique segments the image by placing similar elements into groups, or clusters, based on some similarity measure. Clustering is differ from region growing and shrinking methods, where the mathematical space used for clustering. The details of each methods in segmentation are explained in the next sections.

Thresholding: Thresholding is one of the simplest and most popular method in image segmentation. Two common types of thresholding are outlined as follow:

- Local thresholding is referred when an image is partitioned into subregions and each subregion carry different value of threshold. Local threshold method also called as adaptive thresholding schemes [17-19].
- Global thresholding is referring to assigning only one threshold value to the entire image.

Thresholding techniques also can be categorized into two levels:

- Bilevel thresholding: the image is two (2) regions which are object (black) and background (white).
- Multithresholding: the image is composed of few objects with different surface characteristics thus need multiple value of threshold.

Thresholding also can be analyzed as classification problem, such that classifying bilevel segmentation of an

image into object and background. Among the most common methods found for thresholding in image segmentation are listed as the following:

- Maximum entropy method [20-22].
- Otsu's method (maximum variance) [23-26].
- k-means clustering [27-35].

Edge Detection: There will be edge and line detection in segmentation to divide regions into meaningful information. Edge detection techniques: Line detection/line finding = Hough transform [37]. Hough transform is designed specifically to find lines. A line is a collection of edge points (that are adjacent and have the same direction). The Hough algorithm will take a collection of few edge points.

Edge detection techniques [38-53] have been used as the base of another segmentation technique. Basically, edge detection is also an independent process in image processing. Edge detection, or sometimes it is called as edge finding is also closely related to region detection. We need to find the region boundaries first before we can proceed to segment an object from an image. This is because the edges identified by edge detection are frequently disconnected. It means that we have to find the boundaries in order to get the edges.

In segmentation, line detection is done to divide regions into meaningful information. One of line detection technique is Hough transform. Hough transform is designed specifically to detect lines. A line is a collection of edge points (that are adjacent and have the same direction). The Hough algorithm will take a collection of few edge points.

Region-Based Image Segmentation: This technique attempt to classify a particular image into several regions or classes according to the common properties of the image. There are few properties considered for this process which are pattern and texture, intensity values and spectral profiles of the image. In this method, we want to group the regions so that each of the pixels in the region will have similar value of the properties. There are many real applications used this method such as remote sensing, 2D and 3D images [54-55] while there are various models and algorithms used for this technique such as Markov Random Field Model [56-60] and Mumford-Shah Algorithm [61-64].

Compression-Based Methods: In this method, segmentation will be done in a way the image will be compressed based on the similarity of the patterns of textures or boundary shape of the image. This method aims to minimize the length of the data where the optimal segmentation can be achieved. There are few ways on how to calculate the coding length of the data such as Huffman coding or MDL (Minimum Description Length) principle [65-66], where they can be found in previous studies [67-70].

Histogram-Based Methods: #Histogram-based method [71-76] is one of the frequently used for image segmentation techniques. In this method, we will produce a vertical and a horizontal histogram accordingly. This process is to get a group of pixels in vertical and horizontal regions where they will lead to distinguishing the gray levels of the image.

In common, an image will have two regions: background and object. Normally, the background is assigned as one gray level while the object (or also called as subject) is another gray level. Usually, background will secure the largest part of the image so the gray level of it will have larger peak in the histogram compared to the object of the image.

Region-Growing Methods: Region Growing and Shrinking [77-79] technique use row and column (r,c) based image domain. It can be considered as subset of clustering methods, but limited to spatial domain. Spatial domain means The methods can be:

- Local : operating on small neighbourhoods, or.
- Global : operating on the entire image, or.
- Combination of both.

Split-and-Merge Methods: There is an alternative for segmentation method called split and merge [100-108]. Split and merge is also called as quadtree segmentation where it based on quadtree partition. The data structure used in split and merge is called quadtree where a tree which has nodes and each node can have four children. It divides regions that do not pass a homogeneity test and combines regions that pass the homogeneity test.

For this, we propose the following algorithm, where the pseudo-code can be simplified as the following:

- To get width of y-axis of the image to divide into subregion.



Fig. 8: Image output after segmentation process

- To get width of y-axis of the image to divide into subregion.
- To divide into subregion.
- To remove blank space.
- To get same size after region has been divided.

The example output can be viewed as Figure 8.

To wrap up, a good segmentation process should turn out uniform and homogeneous regions with respect to some characteristics such as gray tone or texture as well as simple regions without many small holes. The output from the segmentation will be used in the next stage which is character recognition.

Character Recognition: Character recognition is the most important task in recognizing the plate number [109]. The recognition of characters has been a problem that has received much attention [110, 111] in the fields of image processing, pattern recognition and artificial intelligence. It is because there is a lot of possibility that the character produced from the normalization step differ from the database. The same characters may differ in sizes, shape and style [110] that could result in recognition of false character and affect the effectiveness and increase the complexity of the whole system. In Malaysian car plate, there are two groups of character, which is alphabet and numeric. It is important for the system to differentiate the character correctly as sometimes the system may confuse due to the similarities in the form of shape.

When a plate number is put for visual recognition, it is expected to be consisting of one or more characters. However, it may also contain the unwanted information; for example, it may contain pictures and colors that do not provide any useful information to recognize the plate number. Thus, the image is first processed for noise reduction and normalization [111, 112]. Noise reduction is to ensure that the image is free from noise [112]. The normalization is where the isolated characters are resized to fit the characters into a binary window and form the input for recognition process [111, 112]. The characters are segment into a block that contains no extra white spaces in all side of the characters.

Next is the process of digitization [110]. Digitization of an image is converting the individual character into binary matrix based on the specified dimensions.




Fig. 9: Image digitization

This process will ensure the uniformity of dimensions between the input and stored patterns in the database. For example, in Figure 9, the alphabet A has been digitized into $24 \times 15 = 360$ binary matrix, each having either black or white color pixel [113, 114, 117, 118]. It is important to convert the data into meaningful information. A binary image function can then be assign for each black pixel, the value is 0 (background) and for each white pixel, the value is 1 (foreground) [113, 115].

There are a few methods applied for the recognition of characters like template matching, feature extraction, geometric approach, neural network, support vector machine, Hidden Markov Model and Bayes net [111, 112, 116].

Template Matching: Template matching is a technique to identify the segmented character [114] by finding the small part in image that match with the template. This method need character image as their template to store in the database [111]. The identification is done by calculating the correlation coefficient where the template the score the highest coefficient is identified as the character of the input [111, 112]. There are three type of matching factor that represent the output which are exact matching, complete mismatching and confused matching [120]. However, due to some similarities in characters, there might be some error during the recognition [121]. Example of character similarities are like, B and 8 or 3, S and 5, Q and G or 0. It should be noted that the size of input image and the template must be exactly the same [114].

Neural Network: A Multi-Layer Perceptron Neural Network (MLP NN) [113, 115] in Figure 10 is commonly used in pattern recognition. MLP has been used to solve various problems by training it in supervise learning with the back-propagation algorithm [109, 110, 115, 119].




Fig. 10: Multilayer perceptron in neural network

The training is done in order to make the input leads to a specific target output [111, 116]. The initial weight is randomly generated and iteratively modified [113]. The weight is modified using the error between the corresponding outputs with desired output. Neural network learns through updating their weight [110]. The purpose of adjusting the weight is to make the output closer to the desired output. It is very important to expand the size of training database in neural network because the efficiency and accuracy of the character recognition will be improved [109].

Chain Code: Chain code is one of the techniques that are able to do the character recognition process [122]. It is one of the shape representations that are used to represent a boundary of a connected sequence of straight line segments [122]. The representation is based on 4-connectivity and 8-connectivity of the segment that may proceed in clockwise or in anticlockwise direction like in Figure 11 [122, 123, 125]. Collision might be occurred when there is multi-connectivity in the character and thus multiple chain codes is produces to represent the segment of the character [123, 126]. Besides, the same character might produce different chain code depend on the starting point and their connectivity direction [124]. Thus in order to standardize the character recognition, some additional parameter is needed and calculated [126]. Some constant parameters that need to justify are segment slope angle, character height and the index in the row [126].

Hidden Markov Model: Hidden Markov Model (HMM) is another common used technique for character recognition. HMM is a probabilistic technique [127, 128] that is widely used in pattern recognition area like speech recognition, biological sequence and modeling [129, 130]. A HMM is defined as a doubly stochastic process that is not directly observable (hidden), but can only be observed through another set of stochastic process that produce the sequence of observed character [129, 131].




Fig. 11: Direction number for 4-directional chain code and 8-directional chain code adapted from N.A. Jusoh, J.M




Fig. 12: Hidden Markov Model topology for license plate image adapted from S.A. Daramola, E. Adetiba, *et al.* [127]



Fig. 13: Image output after character recognition process

For character recognition, two main approaches are used to construct the model, either for each character or for each word [129]. The advantage of this technique is that it has the ability to learn the similarities and differences between the image samples [127]. For training stage, the sample image must be exactly the same size with the images to deal with [132]. The license plate is represented as a sequence of state as Figure 12, which can generate the observation vector, based on the associated probability distribution. The transition probability is responsible to observe the transition occurred between the states [131, 133]. The parameters or probabilities in HMM are trained using the observation vector extracted from the image samples of license plate [127, 131].

The example output can be viewed as Figure 13. The output from the recognition process will be the final output of the license plate recognition in this framework of study.

CONCLUSION

To conclude this paper, we have presented the review of image processing techniques for license plate recognition with various approaches. The experiment has been done in MATLAB to show the basic process of the image processing especially for license plate in Malaysia case study. There are many more techniques and approaches have been studied for in various stages of image processing as well as there are also lack of studies in image processing stages, for example Pal and Pal in [Z1] reveals that earlier reviews on colour image segmentation have not given much attention.

ACKNOWLEDGEMENTS

We would like to acknowledge the Malaysian Technical University Network - Centre of Excellence (MTUN CoE) for the funding granted, MTUN/ 2012/ UTeM-FTMK/11 M00019. We also would like to thank all friends and colleagues for their helpful comments and courage.

REFERENCES

1. Zhiwen, W.A.N.G. and L.I. Shaozi, 0000. "Research an Implement for Vehicle License Place Recognition Based on Improved BP Network."
2. Malviya, A. and S.G. Bhirud, 0000. "Image Fusion of Digital Images."
3. Koval, V., V. Turchenko, V. Kochan, A. Sachenko and G. Markowsky, 0000. "Smart License Plate Recognition System Based on Image Processing Using Neural Network."
4. Parisi, R., E.D. Di Claudio, G. Licarelli and G. Orlandi, 0000. "Car Plate Recognition By Neural Networks and Image Processing."
5. Kumar, Parasuraman and P. Vasantha Kumar, 2002. An Efficient Method for Indian Vehicle License. *Pattern Recognition*, 35: 2279-2301.
6. Plate Extraction and Character Segmentation, 2010. *IEEE International Conference on Computational Intelligence and Computing Research*.
7. Vahid Abolghasemi and Alireza Ahmadyfard, 2009. An edge-based color-aided method for license plate detection, *Image and Vision Computing*, 27: 1134-1142.
8. Nijhuis, J.A.G., M.H. Ter Brugge and K.A. Helmholt, 0000. *Car License Plate Recognition with Neural Networks and Fuzzy Logic*.

9. Abolghasemi, V. and A. Ahmadyfard, 2009. An-edge-based color aided method for license plate detection In: Image and Vision Computing., 27: 1135-1142.
10. Zheng, D., Y. Zhao and J. Wang, 2005. A efficient method of license plate location. In: Pattern Recognition Letters., 26: 2431-2438.
11. Zhu, W.G., G.J. Hou and X. Jia, 2002. A study of locating vehicle license plate based on color feature and mathematical morphology. In: 6th Internat. Conf. on Signal Process., 1: 748-751.
12. Wei, W., M.J. Waang and Z.X. Huang, 2001. An automatic method of location for number-plate using color features. In: Proc. Internat. Conf. on Image Process, 2: 782-785.
13. Jusoh, N.A. and J.M. Zain, 2009. Application of freeman chain codes: an alternative recognition technique for malaysian car plates. In: International Journal of Computer Science and Network Security, 9: 223-227.
14. Chang, S.L., L.S. Chen, Y.C. Chung and S.W. Chen, 2004. Automatic license plate recognition., In: IEEE Transactions on Intelligent Transportation System, 5: 43-53.
15. Hertz, L. and R.W. Schafer, 1988. "Multilevel Thresholding Using Edge Matching" Computer Visual Graph Image Process, 44: 279-295.
16. Umbaugh, S.E., 2005. "Computer Imaging Digital Analysis and Processing," A CRC Press Book.
17. Haralick, R.M. and L.G. Shapiro, 1985. Survey: Image Segmentation Techniques. Computer Vision Graphics and Image Process, 29: 100-132.
18. Siddhartha Bhattacharyya, Ujjwal Maulik and Paramartha Dutta, 2011. Multilevel Image Segmentation With Adaptive Image Context Based Thresholding. Applied Soft Computing, 11(1): 946-962.
19. Nong Sang, Heng Li, Weixue Peng and Tianxu Zhang, 2007. Knowledge-Based Adaptive Thresholding Segmentation Of Digital Subtraction Angiography Images. Image and Vision Computing, 25(8): 1263-127.
20. Zhang, J., C.H. Yan, C.K. Chui and S.H. Ong, 2010. Fast segmentation of bone in CT images using 3D adaptive thres holding. Computers in Biology and Medicine, 40(2): 231-236.
21. Du Feng, Shi Wenkang, Chen Liangzhou, Deng Yong and Zhu Zhe, 2005. Infrared image segmentation with 2-D maximum entropy method based on particle swarm optimization (PSO) Pattern Recognition Letters, 26(5): 597-603.
22. Wen-Bing Tao, Jin-Wen Tian and Jian Liu, 2003. Image Segmentation By Three-Level Thresholding Based On Maximum Fuzzy Entropy And Genetic Algorithm. Pattern Recognition Letters, 24(16): 3069-3078.
23. Xie, J. and H.T Tsui, 2004. Image segmentation based on maximum-likelihood estimation and optimum entropy-distribution (MLE-OED). Pattern Recognition Letters, 25(10): 1133-1141.
24. Liu, C.C., C.Y. Tsai, J. Liu, C.Y. Yu and S.S. Yu, 2012. "A pectoral muscle segmentation algorithm for digital mammograms using Otsu thresholding and multiple regression analysis," Computers and Mathematics with Applications, 64(5): 1100-1107.
25. Chen, Q., L. Zhao, J. Lu, G. Kuang, N. Wang and Y. Jiang, 2012. "Modified two-dimensional Otsu image segmentation algorithm and fast realisation," IET Image Processing, 6(4): 426-433.
26. Xiangyang Xu, Shengzhou Xu, Lianghai Jin and Enmin Song, 2011. "Characteristic analysis of Otsu threshold and its applications," Pattern Recognition Letters, 32(7): 956-961.
27. Deng-Yuan Huang and Chia-Hung Wang, 2009. "Optimal multi-level thresholding using a two-stage Otsu optimization approach," Pattern Recognition Letters, 30(3): 275-284.
28. Choong, M.Y., W.L. Khong, W.Y. Kow, L. Angeline and K.T.K. Teo, 2012. "Graph-based image segmentation using k-means clustering and normalised cuts," Proceedings - 2012 4th International Conference on Computational Intelligence, Communication Systems and Networks, CICSyN 2012, Art. No. 6274360, 2012, pp: 307-312.
29. Siddiqui, F.U. and N.A.M. Isa, 2012. "Optimized K-means (OKM) clustering algorithm for image segmentation," Opto-electronics Review, 20(3): 216-225.
30. Max Mignotte, 2011. "A de-texturing and spatially constrained K-means approach for image segmentation Pattern Recognition Letters," 32(2): 359-367.
31. Clausi, D.A., 2002. "K-means Iterative Fisher (KIF) unsupervised clustering algorithm applied to image texture segmentation," Original Research Article Pattern Recognition, 35(9): 1959-1972.
32. Wen-Liang Hung, Yen-Chang Chang and E. Stanley Lee, 2011. "Weight selection in *W*-K-means algorithm with an application in color image segmentation," Original Research Article Computers and Mathematics with Applications, 62(2): 668-676.

33. Javier Herrera, P., Gonzalo Pajares and María Guijarro, 2011. "A segmentation method using Otsu and fuzzy k-Means for stereovision matching in hemispherical images from forest environments," Original Research Article Applied Soft Computing, 11(8): 4738-474.
34. Li-Hong Juang and Ming-Ni Wu, 2010. "MRI brain lesion image detection based on color-converted K-means clustering segmentation," Original Research Article Measurement, 43(7): 941-949.
35. Li-Hong Juang and Ming-Ni Wu, 2011. "Psoriasis image identification using k-means clustering with morphological processing," Original Research Article Measurement, 44(5): 895-905.
36. Sundar P.V. Balakrishnan, Martha C. Cooper, Varghese S. Jacob and Phillip A. Lewis, 1996. "Comparative performance of the FSCL neural net and K-means algorithm for market segmentation," Original Research Article European Journal of Operational Research, 93(2): 346-357.
37. Chi-Han Chung, Shyi-Chyi Cheng and Chin-Chun Chang, 2010. "Adaptive image segmentation for region-based object retrieval using generalized Hough Transform," Pattern Recognition, 43(10): 3219-3232.
38. Hongzhi Wang and John Oliensis, 2010. "Generalizing edge detection to contour detection for image segmentation," Original Research Article Computer Vision and Image Understanding, 114(7): 731-744.
39. Mo Dai, Pierre Baylou, Louis Humbert, Mohamed Najim, 1996. "Image segmentation by a dynamic thresholding using edge detection based on cascaded uniform filters," Original Research Article Signal Processing, 52(1): 49-63.
40. Jing Huang, Xinge You, Yuan Yan Tang, Liang Du and Yuan Yuan, 2009. "A novel iris segmentation using radial-suppression edge detection," Original Research Article Signal Processing, 89(12): 2630-2643.
41. Ye Zhou, John Starkey and Lalu Mansinha, 2004. "Segmentation of petrographic images by integrating edge detection and region growing," Original Research Article Computers and Geosciences, 30(8): 817-831.
42. Karina Waldemark, Thomas Lindblad, Vlatko Beëanoviæ, Jose L.L. Guillen and Phillip L. Klingner, 2000. "Patterns from the sky: Satellite image analysis using pulse coupled neural networks for pre-processing, segmentation and edge detection," Pattern Recognition Letters, 21(3): 227-237.
43. Yu Xiaohan, Juha Ylä-Jääski and Yuan Baozong, 1991. "A new algorithm for texture segmentation based on edge detection," Original Research Article Pattern Recognition, 24(11): 1105-1112.
44. William E. Higgins and Chaoming Hsu, 1994. "Edge detection using two-dimensional local structure information," Original Research Article Pattern Recognition, 27(2): 277-294.
45. Ali Etemad, S. and Tony White, 2011. "An ant-inspired algorithm for detection of image edge features," Original Research Article Applied Soft Computing, 11(8): 4883-4893.
46. Tan, T.N., 1995. "Texture edge detection by modelling visual cortical channels," Original Research Article Pattern Recognition, 28(9): 1283-1298.
47. Ardeshir Goshtasby, Hai-Lun Shyu, 1995. "Edge detection by curve fitting," Original Research Article Image and Vision Computing, 13(3): 169-177.
48. Sugata Ghosal and Rajiv Mehrotra, 1993. "Orthogonal moment operators for subpixel edge detection," Original Research Article Pattern Recognition, 26(2): 295-306.
49. Xiaoyi Jiang and Horst Bunke, 1999. "Edge Detection in Range Images Based on Scan Line Approximation," Original Research Article Computer Vision and Image Understanding, 73(2): 183-199.
50. Chen, T., Q.H. Wu, R. Rahmani-Torkaman and J. Hughes, 2002. "A pseudo top-hat mathematical morphological approach to edge detection in dark regions," Original Research Article Pattern Recognition, 35(1): 199-210.
51. Zhengchun Lin, Jinshan Jiang and Zhiyan Wang, 2011. "Edge detection in the feature space," Original Research Article Image and Vision Computing, 29(2-3): 142-154.
52. Srinivasan, V., P. Bhatia and S.H. Ong, 1994. "Edge detection using a neural network," Original Research Article Pattern Recognition, 27(12): 1653-1662.
53. Marte A. Ramírez-Ortegón, Ernesto Tapia, Lilia L. Ramírez-Ramírez, Raúl Rojas and Erik Cuevas, 2010. "Transition pixel: A concept for binarization based on edge detection and gray-intensity histograms," Original Research Article Pattern Recognition, 43(4): 1233-1243.
54. Zhongwu Wang, John R. Jensen and Jungho Im, 2010. "An automatic region-based image segmentation algorithm for remote sensing applications. Environmental Modelling and Software, 25(10): 1149-1165.

55. Hepzibah A. Christinal, Daniel Díaz-Pernil and Pedro Real, 2011. Region-based segmentation of 2D and 3D images with tissue-like P systems Original Research Article Pattern Recognition Letters, 32(16): 2206-2212.
56. Chung-Lin Huang, Tai-Yuen Cheng and Chaur-Chin Chen, 1992. Color images' segmentation using scale space filter and markov random field. Pattern Recognition, 25(10): 1217-1229.
57. Kim, Y. and Hyun S. Yang, 1994. A systematic way for region-based image segmentation based on Markov Random Field model. Pattern Recognition Letters, 15(10): 969-976.
58. Zoltan Kato and Ting-Chuen Pong, 2006. A Markov random field image segmentation model for color textured images. Image and Vision Computing, 24(10): 1103-1114.
59. Xiao Wang and Han Wang, 2004. Markov random field modeled range image segmentation. Pattern Recognition Letters, 25(3): 367-375.
60. Barker, S.A. and P.J.W. Rayner, 2000. Unsupervised image segmentation using Markov random field models. Pattern Recognition, 33(4): 587-602.
61. Alfonso Vitti, 2012. The Mumford–Shah Variational Model For Image Segmentation: An Overview Of The Theory, Implementation And Use. ISPRS Journal of Photogrammetry and Remote Sensing, 69: 50-64.
62. Xiaojun Du, Wumo Pan and Tien D. Bui, 2009. Text Line Segmentation In Handwritten Documents Using Mumford-Shah Model. Pattern Recognition, 42(12): 3136-3145.
63. Noha El-Zehiry, Prasanna Sahoo and Adel Elmaghraby, 2011. Combinatorial Optimization Of The Piecewise Constant Mumford-Shah Functional With Application To Scalar/Vector Valued And Volumetric Image Segmentation. Image and Vision Computing, 29(6): 365-381.
64. Jin-Ping Song and Shuai-Jie Li, 2007. An Improved Mumford-Shah Model and Its Applications to Image Processing with the Piecewise Constant Level Set Method. Acta Automatica Sinica, 33(12): 1259-1262.
65. Lena Chang, 2004. Multispectral image compression using eigenregion-based segmentation. Pattern Recognition, 37(6): 1233-1243.
66. Ragnar Nohre, 1995. Computer vision: Compress to comprehend. Pattern Recognition Letters, 16(7): 711-717.
67. Sambhunath Biswas, 2003. "Segmentation based compression for graylevel images," Original Research Article Pattern Recognition, 36(7): 1501-1517.
68. Yibing Yang, Hong Yan and Donggang Yu, 2000. "Content-lossless document image compression based on structural analysis and pattern matching," Original Research Article Pattern Recognition, 33(8): 1277-1293.
69. Chung-Tao Chu, Dimitris Anastassiou and Shih-Fu Chang, 1997. "Hybrid object-based/block-based coding in video compression at very low bit-rate," Original Research Article Signal Processing: Image Communication, 10(1-3): 159-171.
70. Robert J. Bonneau and Henry E. Meadows, 2001. "A Multiresolution Markov Approach to Model-Based Image Compression," Original Research Article Digital Signal Processing, 11(4): 346-358.
71. Kun Qin, Kai Xu, Feilong Liu and Deyi Li, 2011. "Image segmentation based on histogram analysis utilizing the cloud model," Original Research Article Computers and Mathematics with Applications, 62(7): 2824-2833.
72. Alireza Khotanzad, Abdelmajid Bouarfa, 1990. "Image segmentation by a parallel, non-parametric histogram based clustering algorithm," Original Research Article Pattern Recognition, 23(9): 961-973.
73. Bonnet, N., J. Cutrona and M. Herbin, 2002. "A 'no-threshold' histogram-based image segmentation method," Pattern Recognition, 35(10): 2319-2322.
74. Guang-Hai Liu and Jing-Yu Yang, 2013. "Content-based image retrieval using color difference histogram," Original Research Article Pattern Recognition, 46(1): 188-198.
75. Mohammad J. Abdollahifard, Karim Faez, Mohammadreza Pourfard and Mojtaba Abdollahi, 2011. "A histogram-based segmentation method for characterization of self-assembled hexagonal lattices," Original Research Article Applied Surface Science, 257(24): 10443-10450.
76. Nakib, A., H. Oulhadj and P. Siarry, 2007. "Image histogram thresholding based on multiobjective optimization," Original Research Article Signal Processing, 87(11): 2516-2534.
77. Liu, J., Y. Ma, K. Chen and S.B. Li, 2012. "A novel color image segmentation method based on improved region growing," Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics) 7530 LNAI, pp: 365-373.
78. Angelina, S., L.P. Suresh and S.H.K. Veni, 2012. "Image segmentation based on genetic algorithm for region growth and region merging," International Conference on Computing, Electronics and Electrical Technologies, ICCEET, Art. No. 6203833, pp: 970-974.

79. Ye Zhou, John Starkey and Lalu Mansinha, 2004. "Segmentation of petrographic images by integrating edge detection and region growing," Original Research Article Computers and Geosciences, 30(8): 817-831.
80. Chung-Chia Kang, Wen-June Wang and Chung-Hao Kang, 2012. "Image segmentation with complicated background by using seeded region growing," Original Research Article AEU - International Journal of Electronics and Communications, 66(9): 767-771.
81. Jean-Philippe Thiran, Vincent Warscotte and Benoît Macq, 1997. "A queue-based region growing algorithm for accurate segmentation of multi-dimensional digital images," Original Research Article Signal Processing, 60(1): 1-10.
82. Chantal Revol and Michel Jourlin, 1997. "A new minimum variance region growing algorithm for image segmentation," Original Research Article Pattern Recognition Letters, 18(3): 249-258.
83. Moghaddamzadeh, A. and N. Bourbakis, 1997. "A fuzzy region growing approach for segmentation of color images," Original Research Article Pattern Recognition, 30(6): 867-881.
84. Peter, Z., V. Bousson, C. Bergot and F. Peyrin, 2008. "A constrained region growing approach based on watershed for the segmentation of low contrast structures in bone micro-CT images," Original Research Article Pattern Recognition, 41(7): 2358-2368.
85. Alain, Tremeau and Nathalie Borel, 1997. "A region growing and merging algorithm to color segmentation," Original Research Article Pattern Recognition, 30(7): 1191-1203.
86. Maria Dolores Gil Montoya, C. Gil and I. Garcí'a, 2003. "The load unbalancing problem for region growing image segmentation algorithms," Original Research Article Journal of Parallel and Distributed Computing, 63(4): 387-395.
87. Yian-Leng Chang and Xiaobo Li, 1995. "Fast image region growing," Original Research Article Image and Vision Computing, 13(7): 559-571.
88. Aminah Abdul Malek, Wan Eny Zarina Wan Abdul Rahman, Arsmah Ibrahim, Rozi Mahmud, Siti Salmah Yasiran and Abdul Kadir Jumaat, 2010. "Region and Boundary Segmentation of Microcalcifications using Seed-Based Region Growing and Mathematical Morphology," Original Research Article Procedia - Social and Behavioral Sciences, 8: 634-639.
89. Maria Kallergi, Kevin Woods, Laurence P. Clarke, Wei Qian and Robert A. Clark, 1992. "Image segmentation in digital mammography: Comparison of local thresholding and region growing algorithms," Original Research Article Computerized Medical Imaging and Graphics, 16(5): 323-331.
90. Hazem M. Raafat Andrew and K.C. Wong, 1988. "A texture information-directed region growing algorithm for image segmentation and region classification," Original Research Article Computer Vision, Graphics and Image Processing, 43(1): 1-21.
91. Ye Zhou, John Starkey and Lalu Mansinha, 2004. "Segmentation of petrographic images by integrating edge detection and region growing," Original Research Article Computers and Geosciences, 30(8): 817-831.
92. Todd R. Reed, Harry Wechsler, Michael Werman, 1990. "Texture segmentation using a diffusion region growing technique," Original Research Article Pattern Recognition, 23(9): 953-960.
93. Hazem M. Raafat Andrew and K.C. Wong, 1988. "A texture information-directed region growing algorithm for image segmentation and region classification," Computer Vision, Graphics and Image Processing, 42(1): 133-134.
94. Michel Kocher and Riccardo Leonardi, 1986. "Adaptive region growing technique using polynomial functions for image approximation," Original Research Article Signal Processing, 11(1): 47-60.
95. Andrew Mehnert and Paul Jackway, 1997. "An improved seeded region growing algorithm," Original Research Article Pattern Recognition Letters, 18(10): 1065-1071.
96. Jean-Pierre Gambotto, 1993. "A new approach to combining region growing and edge detection," Original Research Article Pattern Recognition Letters, 14(11): 869-875.
97. Marc Willebeek-Lemair and Anthony P. Reeves, 1990. "Solving nonuniform problems on SIMD computers: Case study on region growing," Original Research Article Journal of Parallel and Distributed Computing, 8(2): 135-149.
98. Copty, N., S. Ranka, G. Fox and R.V. Shankar, 1994. "A Data Parallel Algorithm for Solving the Region Growing Problem on the Connection Machine," Journal of Parallel and Distributed Computing, 21(1): 160-168.

99. Bir Bhanu and Wilhelm Burger, 1988. "Approximation of displacement fields using wavefront region growing," Original Research Article Computer Vision, Graphics and Image Processing, 41(3): 306-322.
100. Guillaume, Damiand and Patrick Resch, 2003. "Split-and-merge algorithms defined on topological maps for 3D image segmentation," Original Research Article Graphical Models, 65(1-3): 149-167.
101. Shih-Yung Chen, Wei-Chung Lin and Chin-Tu Chen, 1991. "Split-and-merge image segmentation based on localized feature analysis and statistical tests," Original Research Article CVGIP: Graphical Models and Image Processing, 53(5): 457-475.
102. Manousakas, I.N., P.E. Udrill, G.G. Cameron and T.W. Redpath, 1998. "Split-and-Merge Segmentation of Magnetic Resonance Medical Images: Performance Evaluation and Extension to Three Dimensions," Original Research Article Computers and Biomedical Research, 31(6): 393-412.
103. Lifeng Liu and Stan Sclaroff, 2004. "Deformable model-guided region split and merge of image regions," Original Research Article Image and Vision Computing, 22(4): 343-354.
104. Vincent Barra, 2006. "Robust segmentation and analysis of DNA microarray spots using an adaptative splitand merge algorithm," Original Research Article Computer Methods and Programs in Biomedicine, 81(2): 174-180.
105. Zhihua Zhang, Chibiao Chen, Jian Sun and Kap Luk Chan, 2003. "EM algorithms for Gaussian mixtures with split-and-merge operation," Original Research Article Pattern Recognition, 36(9): 1973-1983.
106. Robert H. Laprade, 1988. "Split-and-merge segmentation of aerial photographs," Computer Vision, Graphics and Image Processing, 44(1): 77-86.
107. Karel C. Strasters, and Jan J. Gerbrands, 1991. "Three-dimensional image segmentation using a split, merge and group approach," Original Research Article Pattern Recognition Letters, 12(5): 307-325.
108. Matti Pietikäinen, Azriel Rosenfeld and Ingrid Walter, 1982. "Split-and-link algorithms for image segmentation," Original Research Article Pattern Recognition, 15(4): 287-298.
109. Nagare, A.P., 0000. "License Plate Character Recognition System using Neural Network", International Journal of Computer Application, 25(10).
110. Shashank Araokar, 0000. "Visual Character Recognition using Artificial Neural Networks."
111. Indira, B., M. Shalini, M.V.R. Murthy and M.S. Shaik, 0000. "Classification and Recognition of Printed Hindi Characters using Artificial Neural Networks."
112. Jin, L., H. Xian, J. Bie, Y. Sun, H. Hou and Q. Niu, 0000. "License Plate Recognition Algorithm for Passanger Cars in Chinese Residential Areas", ISSN 1424-8220.
113. Otham Khalifa, Sheroz Khan, Rafiqul Islam and Ahmad Suleiman, 2007. "Malaysian Vehicle License Plate Recognition", The International Arab Journal of International Technology, 4(4).
114. Zakaria, M.F. and S.A. Suandi, 2010. "Malaysian Car Number Plate Detection System Based on Template Matching and Colour Information", International Journal on Computer Science and Engineering, 2(4).
115. Stuti Asthana, Niresh Sharma and Rajdeep Singh, 0000. "Vehicle Number Plate Recognition using Multiple Layer Back Propagation Neural Networks", International Journal of Computer Technology and Electronics Engineering, 1(1).
116. Anagnostopoulos, C.N.E., I.E. Anagnostopoulos, V. Loumos and E. Kayafas, 2006. "A License Plate-Recognition Algorithm for Intelligent Transportation System Applications", IEEE Transactions of Intelligent Transportation Systems, 7(3).
117. Zafar, M.F., D. Mohamad and R.M. Othman, 0000. "On-line Handwritten Character Recognition: An Implementation of Counterpropagation Neural Net."
118. Meshesha, M. and C.V. Jawahar, 0000. "Optical Character Recognition of Amharic Documents."
119. Maarif, H.A. and Sar Sardy, 0000. "Plate Number Recognition by using Artificial Neural Network."
120. Saha, S., S. Basu and M. Nasipuri, 2011. "Automatic Localization and Recognition of License Plate Characters for Indian Vehicles", International Journal of Computer Science and Emerging Technologies, 2(4).
121. Guhe, A., S. Deshmukh, B. Borekar, A. Kailaswar and M.E. Rane, 2012. "Coal Mines Security System", International Journal of Computer Science Issues, 9(3).
122. Jusoh, N.A. and J.M. Zain, 2009. "Application of Freeman Chain Codes: An Alternative Recognition Technique for Malaysian Car Plates", International Journal of Computer Science and Network Security, 9(11).

123. Sangame, S.K., R.J. Ramteke and V.G. Yogesh, 2011. "Recognition Of Isolated Handwritten Kannada Characters Using Invariant Moments And Chain Code", World Journal of Science and Technology, ISSN: 2231-2587.
124. Sulaiman, A., M.N. Sulaiman, M. Othman and R. Wirza, 2010. "Chain Coding and Pre Processing Stages of Handwritten Character Image File", Electronic Journal of Computer Science and Information Technology, 2(1).
125. Madhvanath, S., G. Kim and V. Govindaraju, 1999. "Chaincode Contour Processing for Handwritten Word Recognition" IEEE Transactions on Pattern Analysis and Machine Intelligence, 21(9).
126. Sarukhanyan, H., S. Alaverdyan and G. Petrosyan, 0000. "Automatic Number Plate Recognition System."
127. Daramola, S.A., E. Adetiba, A.U. Adoghe, J.A. Badejo, I.A. Samuel and T. Fagorusi, 2011. "Automatic Vehicle Identification System Using License Plate", Internatinal Journal of Engineering Science and Technology, 3(2).
128. Poritz A.B., 1988. "Hidden Markov Models: A Guided Tour", IEEE.
129. Aas, K., L. Eikvil and T. Andersen, 0000. "Text Recognition from Grey Level Images Using Hidden Markov Models."
130. Paul D.B., 0000. "Speech Recognition Using Hidden Markov Models."
131. Phil Blunsom, 2004. "Hidden Markov Models".
132. Duan, T.D., T.L.H. Du, T.V. Phuoc and N.V. Hoang, 2005. "Building an Automatic Vehicle License-Plate Recognition System", International Conference in Computer Science.
133. "Hidden Markov Models With Duration-Dependent State Transition Probabilities", Electronics Letters, 27(8).
134. Yong W.E., 0000. "Vehicle License Plate Registration Recognition System."