

## Prediction of Egg Mass Based on Some Geometrical Characteristics

*Fereydoun Keshavarzpour*

Department of Agriculture,  
Shahr-e-Rey Branch, Islamic Azad University, Tehran, Iran

**Abstract:** In this study, nine linear regression models for predicting egg mass from some geometrical characteristics of egg such as length (L), diameter (D), geometrical mean diameter (GMD), first projected area ( $PA_1$ ), second projected area ( $PA_2$ ), criteria area (CAE) and estimated volume or volume calculated from an oblate spheroid assumed shape ( $V_{OSP}$ ) were suggested. Models were divided into three main classifications and the egg mass was estimated as a function of some independent variables. The statistical results of the study indicated that in order to predict egg mass based on outer dimensions, the mass model based on geometrical mean diameter as  $M = -24.42 + 1.67 \text{ GMD}$  with  $R^2 = 0.595$  and the mass model based on length and diameter as  $M = -27.81 + 0.69 L + 1.01 D$  with  $R^2 = 0.619$  can be recommended. Also, to predict egg mass based on projected areas, the mass model based on the first projected area as  $M = 13.12 + 2.16 PA_1$  with  $R^2 = 0.599$  can be suggested. These models can be used to design and develop sizing machines equipped with an image processing system.

**Key words:** Egg mass • Modeling • Prediction • Geometrical characteristics • Grading

### INTRODUCTION

Egg is considered as one of the basic foodstuffs due to its very high nutritive value. Besides a rich source of protein, it contains a fair amount of nutrients (Sodium, Potassium, Calcium, Phosphorus, Magnesium, Iron, Zinc, Copper, Iodine, Sulfur and Selenium) and vitamins (A, B<sub>1</sub>, B<sub>2</sub>, B<sub>3</sub>, B<sub>6</sub>, B<sub>12</sub>, D and E). Egg contains 87-90% edible portion, 65-70% moisture, 11.0-12.5% protein and 9.5-10.8% oil [1-3].

Egg size is one of the most important quality parameters for evaluation by consumer preference. Consumers prefer eggs of equal size and shape [3]. Sorting can increase uniformity in size and shape, reduce packaging and transportation costs and also may provide an optimum packaging configuration [4-7]. Moreover, sorting is important in meeting quality standards, increasing market value and marketing operations [8-10]. Sorting manually is associated with high labour costs in addition to subjectivity, tediousness and inconsistency which lower the quality of sorting [11]. However, replacing human with a machine may still be questionable where the labour cost is comparable with the sorting equipment [12]. Studies on sorting in recent years

have focused on automated sorting strategies (eliminating human efforts) to provide more efficient and accurate sorting systems which improve the classification success or speed up the classification process [13, 14].

The size of produce is frequently represented by its mass because it is relatively simple to measure. However, sorting based on some geometrical characteristics may provide a more efficient method than mass sorting. Moreover, the mass of produce can be easily estimated from geometrical characteristics if the mass model of the produce is known [15]. Therefore, modeling of egg mass based on some geometrical characteristics may be useful and applicable. Physical characteristics of products are the most important parameters in design of sorting systems. Among these physical characteristics, mass, projected area and center of the gravity are the most important ones in sizing systems [16]. Other important parameters are outer dimensions [17-19].

Therefore, the main objectives of this research were: (a) to determine optimum mass model (s) based on some geometrical characteristics of egg and (b) to verify determined mass model(s) by comparing their results with those of the measuring method.

## MATERIALS AND METHODS

**Experimental Procedure:** Ninety randomly selected eggs of various sizes were purchased from a local market. Eggs were selected for freedom from defects by careful visual inspection, transferred to the laboratory and held at  $5\pm 1^\circ\text{C}$  and  $90\pm 5\%$  relative humidity until experimental procedure.

In order to obtain required parameters for determining mass models, the mass of each egg was measured to 0.1 g accuracy on a digital balance. Moreover, the volume of each egg was measured using the water displacement method. Each egg was submerged into water and the volume of water displaced was measured. Water temperature during measurements was kept at  $25^\circ\text{C}$ . The density of each egg was then calculated from the mass divided by the measured volume.

By assuming the shape of eggs as an oblate spheroid, the outer dimensions of each egg, i.e. length (L) and diameter (D) was measured to 0.1 mm accuracy by a digital caliper. The geometric mean diameter (GMD) of each egg was then calculated by equation (1).

$$\text{GMD} = (\text{LD}^2)^{1/3} \quad (1)$$

Two projected areas of each egg, i.e. first projected area ( $\text{PA}_1$ ) and second projected area ( $\text{PA}_2$ ) was also calculated by using equation (2) and equation (3), respectively. The average projected area known as criteria area (CAE) of each egg was then determined from equation (4).

$$\text{PA}_1 = \pi \text{LD}/4 \quad (2)$$

$$\text{PA}_2 = \pi \text{D}^2/4 \quad (3)$$

$$\text{CAE} = (2\text{PA}_1 + \text{PA}_2)/3 \quad (4)$$

In addition, the volume of assumed shape or estimated volume of each egg ( $V_{\text{OSP}}$ ) was calculated by using equation (5). Table 1 shows some physical and geometrical properties of the eggs used to determine mass models.

$$V_{\text{OSP}} = \pi \text{LD}^2/6 \quad (5)$$

Also, in order to verify mass models, physical and geometrical properties of ten randomly selected eggs of various sizes were determined as above-mentioned methods. Table 2 shows some physical and geometrical properties of the eggs used to verify mass models.

**Regression Models:** A typical linear multiple regression model is shown in equation (6):

$$Y = k_0 + k_1X_1 + k_2X_2 + \dots + k_nX_n \quad (6)$$

Where:

Y = Dependent variable, for example mass of egg  
 $X_1, X_2, \dots, X_n$  = Independent variables, for example geometrical characteristics of egg  
 $k_0, k_1, k_2, \dots, k_n$  = Regression coefficients

In order to estimate egg mass from geometrical characteristics, nine linear regression mass models were suggested. Models were divided into three main classifications (Table 3).

**Statistical Analysis:** A paired samples t-test was used to compare the egg mass values predicted using models with the egg mass values measured by digital balance. Also, to check the discrepancies between the egg mass values measured by digital balance with the egg mass values predicted by mass models, root mean squared error

Table 1: The mean values, standard deviation (S.D.) and coefficient of variation (C.V.) of some physical and geometrical properties of the 90 randomly selected eggs used to determine mass models

Parameter	Minimum	Maximum	Mean	S.D.	C.V. (%)
Mass (M), g	42.05	58.33	50.73	2.78	5.49
Length (L), mm	50.15	58.85	53.98	1.94	3.59
Diameter (D), mm	38.45	52.30	40.99	1.47	3.59
Geometrical mean diameter (GMD), mm	42.74	54.31	44.92	1.28	2.86
First projected area ( $\text{PA}_1$ ), $\text{cm}^2$	15.91	24.05	17.38	0.99	5.73
Second projected area ( $\text{PA}_2$ ), $\text{cm}^2$	11.61	21.48	13.21	1.03	7.82
Criteria area (CAE), $\text{cm}^2$	14.50	23.19	15.99	0.96	6.00
Estimated volume ( $V_{\text{OSP}}$ ), $\text{cm}^3$	40.87	83.85	47.57	4.62	9.71
Measured volume ( $V_M$ ), $\text{cm}^3$	37.02	49.74	44.22	2.64	5.97
Density ( $\rho$ ), $\text{g cm}^{-3}$	1.060	1.246	1.148	0.036	3.15

Table 2: The mean values, standard deviation (S.D.) and coefficient of variation (C.V.) of some physical and geometrical properties of the ten randomly selected eggs used to verify mass models

Parameter	Minimum	Maximum	Mean	S.D.	C.V. (%)
Mass (M), g	48.26	56.57	52.66	2.63	4.99
Length (L), mm	42.80	55.50	52.94	3.69	6.96
Diameter (D), mm	39.85	42.60	41.70	0.93	2.23
Geometrical mean diameter (GMD), mm	41.90	46.53	45.13	1.40	3.10
First projected area (PA <sub>1</sub> ), cm <sup>2</sup>	13.93	18.57	17.34	1.33	7.69
Second projected area (PA <sub>2</sub> ), cm <sup>2</sup>	12.47	14.25	13.66	0.60	4.42
Criteria area (CAE), cm <sup>2</sup>	13.79	17.13	16.11	1.00	6.20
Estimated volume (V <sub>OSP</sub> ), cm <sup>3</sup>	38.50	52.73	48.24	4.30	8.92
Measured volume (V <sub>M</sub> ), cm <sup>3</sup>	40.27	52.14	46.03	3.25	7.07
Density (ρ), g cm <sup>-3</sup>	1.085	1.210	1.146	0.05	0.04

Table 3: Nine linear regression mass models in three classifications

Model classification	Model No.	Model
First	1	M = k <sub>0</sub> + k <sub>1</sub> L
	2	M = k <sub>0</sub> + k <sub>1</sub> D
	3	M = k <sub>0</sub> + k <sub>1</sub> GMD
	4	M = k <sub>0</sub> + k <sub>1</sub> L + k <sub>2</sub> D
Second	5	M = k <sub>0</sub> + k <sub>1</sub> PA <sub>1</sub>
	6	M = k <sub>0</sub> + k <sub>1</sub> PA <sub>2</sub>
	7	M = k <sub>0</sub> + k <sub>1</sub> CAE
	8	M = k <sub>0</sub> + k <sub>1</sub> PA <sub>1</sub> + k <sub>2</sub> PA <sub>2</sub>
Third	9	M = k <sub>0</sub> + k <sub>1</sub> V <sub>OSP</sub>

(RMSE) and mean relative percentage deviation (MRPD) were calculated using the equations (7) and (8), respectively [20-25]:

$$RMSE = \sqrt{\frac{\sum_{i=1}^n (M_i - M_i^*)^2}{n}} \quad (7)$$

Where:

- RMSR = Root mean squared error, g
- M<sub>i</sub> = Egg mass measured by digital balance, g
- M<sub>i</sub><sup>\*</sup> = Egg mass predicted by mass model, g
- n = Number of samples

$$MRPD = \frac{100 \times \sum_{i=1}^n \frac{|M_i - M_i^*|}{M_i}}{n} \quad (8)$$

Where:

MRPD = Mean relative percentage deviation, %

## RESULTS

For mathematical describing mass models, all the data were subjected to linear regression analysis using the Microsoft Excel (version 2003). The p-value of the independent variables and coefficient of determination (R<sup>2</sup>) of all the linear regression mass models are shown in Table 4.

**First Classification:** In this classification egg mass can be predicted using single variable linear regressions of length (L), diameter (D) and geometrical mean diameter (GMD) of egg or multiple variable linear regression of length and diameter of egg. As indicated in Table 4, among the first classification models (models No. 1-4), model No. 1 and model No. 2 had the lowest R<sup>2</sup> value (0.344 and 0.400, respectively). However, model No. 3 and model No. 4 had the highest R<sup>2</sup> value (0.595 and 0.619, respectively). Model No. 3 and model No. 4 are given in equations (9) and (10), respectively.

$$M = -24.42 + 1.67 \text{ GMD} \quad (9)$$

$$M = -27.81 + 0.69 L + 1.01 D \quad (10)$$

**Second Classification:** In this classification egg mass can be predicted using single variable linear regressions of first projected area (PA<sub>1</sub>), second projected area (PA<sub>2</sub>) and criteria area (CAE) of egg or multiple variable linear regression of first and second projected areas of egg. As indicated in Table 4, among the second classification models (models No. 5-8), model No. 6 and model No. 7 had the lowest R<sup>2</sup> value (0.367 and 0.657, respectively). Conversely, model No. 5 and model No. 8 had the highest R<sup>2</sup> value (0.599 and 0.599, respectively). Model No. 5 and model No. 8 are given in equations (11) and (12), respectively.

$$M = 13.12 + 2.16 \text{ PA}_1 \quad (11)$$

$$M = 13.04 + 2.21 \text{ PA}_1 - 0.06 \text{ PA}_2 \quad (12)$$

**Third Classification:** In this classification egg mass can be predicted using single variable linear regression of estimated volume calculated from an oblate spheroid assumed shape (V<sub>OSP</sub>) of egg. As indicated in Table 4, the R<sup>2</sup> value of model No. 9 was 0.517. Model No. 9 is given in equation (13).

$$M = 30.12 + 0.43V_{OSP} \quad (13)$$

Table 4: Linear regression mass models, p-value of model variable(s) and coefficient of determination (R<sup>2</sup>)

Model No.	p-value							R <sup>2</sup>
	L	D	GMD	PA <sub>1</sub>	PA <sub>2</sub>	CAE	V <sub>OSP</sub>	
1	1.28E-09	-	-	-	-	-	-	0.344
2	-	2.27E-11	-	-	-	-	-	0.400
3	-	-	5.75E-19	-	-	-	-	0.595
4	3.68E-10	6.88E-12	-	-	-	-	-	0.619
5	-	-	-	3.48E-19	-	-	-	0.599
6	-	-	-	-	2.50E-10	-	-	0.367
7	-	-	-	-	-	1.18E-17	-	0.567
8	-	-	-	2.99E-10	0.838043	-	-	0.599
9	-	-	-	-	-	-	1.45E-15	0.517

### DISCUSSION

Among the linear regression models (models No. 1-9), models No. 3, 4 and 5 were chosen due to higher R<sup>2</sup> value and simplicity and a paired samples t-test was used to compare the egg mass values predicted using models No. 3, 4 and 5 with the egg mass values measured by digital balance. Also, to check the discrepancies between the egg mass values predicted by models with the egg mass values measured by digital balance, RMSE and MRPD were calculated.

The egg mass values predicted by model No. 3 were compared with the egg mass values measured by digital balance and are shown in Table 5. The paired samples t-test results indicated that the egg mass values predicted with model No. 3 were significantly less than the egg mass values measured by digital balance (Table 6). The mean egg mass difference between two methods was -1.08 g (95% confidence interval: -2.06 and -0.10 g; P = 0.983). RMSE and MRPD were also used to check the discrepancies between the two methods. The amounts of RMSE and MRPD were 1.7 g and 2.3%, respectively. Thus, egg mass predicted by model No. 3 may be 1.7 g or 2.3% less than egg mass measured by a digital balance.

The egg mass values predicted by model No. 4 were compared with the egg mass values measured by digital balance and are shown in Table 5. The paired samples t-test results indicated that the egg mass values predicted with model No. 4 were significantly less than the egg mass values measured by digital balance (Table 6). The mean egg mass difference between two methods was -1.24 g (95% confidence interval: -2.19 and -0.29 g; P = 0.992). Again, RMSE and MRPD were used to check the discrepancies between the two methods. The amounts of RMSE and MRPD were 1.8 g and 2.4%, respectively. Therefore, egg mass predicted by model No. 4 may be 1.8 g or 2.4% less than egg mass measured by a digital balance.

The egg mass values predicted by model No. 5 were compared with the egg mass values measured by digital balance and are shown in Table 5. The paired samples t-test results indicated that the egg mass values predicted with model No. 5 were significantly less than the egg mass values measured by digital balance (Table 6). The mean egg mass difference between two methods was -1.30 g (95% confidence interval: -2.29 and -0.31 g; P = 0.992). Once more, RMSE and MRPD were used to check the discrepancies between between the two methods.

Table 5: Geometrical characteristics of the ten eggs used in evaluating selected mass models

Sample No.	Geometrical characteristics of egg				Egg mass (g)			
	L (mm)	D (mm)	GMD (mm)	PA <sub>1</sub> (cm <sup>2</sup> )	Measured by digital balance	Predicted by model No. 3	Predicted by model No. 4	Predicted by model No. 5
1	52.7	39.9	43.7	16.5	48.3	48.7	48.7	48.8
2	54.0	40.5	44.6	17.2	50.3	50.2	50.2	50.3
3	52.8	41.5	44.9	17.2	50.3	50.8	50.4	50.3
4	54.3	41.3	45.2	17.6	51.6	51.2	51.2	51.2
5	53.2	42.5	45.8	17.7	52.5	52.1	51.7	51.5
6	53.1	42.2	45.6	17.6	52.8	51.8	51.4	51.2
7	54.7	42.1	45.9	18.1	53.6	52.4	52.3	52.3
8	53.7	42.6	46.0	18.0	54.8	52.6	52.2	52.0
9	55.4	42.0	46.1	18.3	55.8	52.6	52.7	52.7
10	55.5	42.6	46.5	18.6	56.6	53.4	53.4	53.3

Table 6: Paired samples t-test analyses on comparing egg mass determination methods

Determination methods	Average difference (g)	Standard deviation of difference (g)	p-value	95% confidence intervals for the difference in means (g)
Measuring vs. model No. 3	-1.08	1.37	0.983	-2.06, -0.10
Measuring vs. model No. 4	-1.24	1.33	0.992	-2.19, -0.29
Measuring vs. model No. 5	-1.30	1.38	0.992	-2.29, -0.31

The amounts of RMSE and MRPD were 1.9 g and 2.6%, respectively. As a result, egg mass predicted by model No. 5 may be 1.9 g or 2.6% less than egg mass measured by a digital balance.

### CONCLUSIONS

In order to predict egg mass based on some geometrical characteristics, the mass model based on geometrical mean diameter as  $M = -24.42 + 1.67 \text{ GMD}$  with  $R^2 = 0.595$  and the mass model based on length and diameter as  $M = -27.81 + 0.69 L + 1.01 D$  with  $R^2 = 0.619$  can be recommended. Also, to predict egg mass based on projected areas, the mass model based on the first projected area as  $M = 13.12 + 2.16 \text{ PA}_1$  with  $R^2 = 0.599$  can be suggested. These models can be used to design and develop sizing machines equipped with an image processing system.

### REFERENCES

- Hasan, Z.U., J.I. Sultan and M. Akram, 2000. Nutritional manipulation during induced moult in white leghorn layers 2. Effects of percent hen day egg production, body weight and reproductive system. *Int. J. Agric. Biol.*, 2: 318-321.
- Ashraf, M., S. Mahmood and F. Ahmad, 2003. Comparative reproductive efficiency and egg quality characteristics of Lyallpur Silver Black and Rhode Island Red breeds of poultry. *Int. J. Agric. Biol.*, 5: 449-451.
- Rashidi, M., M. Malekiyan and M. Gholami, 2008. Egg volume determination by spheroid approximation and image processing. *World Applied Sci. J.*, 3: 590-596.
- Sadrnia, H., A. Rajabipour, A. Jafary, A. Javadi and Y. Mostofi, 2007. Classification and analysis of fruit shapes in long type watermelon using image processing. *Int. J. Agric. Biol.*, 9: 68-70.
- Rashidi, M. and K. Seyfi, 2007. Classification of fruit shape in kiwifruit applying the analysis of outer dimensions. *Int. J. Agric. Biol.*, 9: 759-762.
- Rashidi, M. and K. Seyfi, 2007. Classification of fruit shape in cantaloupe using the analysis of geometrical attributes. *World J. Agric. Sci.*, 3: 735-740.
- Rashidi, M. and M. Gholami, 2008. Classification of fruit shape in kiwifruit using the analysis of geometrical attributes. *American-Eurasian J. Agric. & Environ. Sci.*, 3: 258-263.
- Wilhelm, L.R., D.A. Suter and G.H. Brusewitz, 2005. *Physical Properties of Food Materials*. Food and Process Engineering Technology. ASAE, St. Joseph, Michigan, USA.
- Rashidi, M. and K. Seyfi, 2008. Determination of cantaloupe volume using image processing. *World Applied Sci. J.*, 2: 646-651.
- Rashidi, M. and K. Seyfi, 2008. Determination of kiwifruit volume using image processing. *World Applied Sci. J.*, 3: 184-190.
- Wen, Z. and Y. Tao, 1999. Building a rule-based machine-vision system for defect inspection on apple sorting and packing lines. *Expert Systems with Application*, 16: 307-713.
- Kavdir, I. and D.E. Guyer, 2004. Comparison of artificial neural networks and statistical classifiers in apple sorting using textural features. *Biosystems Engineering*, 89: 331-344.
- Kleynen, O., V. Leemans and M.F. Destain, 2003. Selection of the most effective wavelength bands for 'Jonagold' apple sorting. *Postharvest Biology and Technology*, 30: 221-232.
- Polder, G., G.W.A.M. Van der Heijden and I.T. Young, 2003. Tomato sorting using independent component analysis on spectral images. *Real-Time Imaging*, 9: 253-259.
- Rashidi, M. and K. Seyfi, 2008. Modeling of kiwifruit mass based on outer dimensions and projected areas. *American-Eurasian J. Agric. & Environ. Sci.*, 3: 14-17.
- Malcolm, E.W., J.H. Toppan and F.E. Sister, 1986. The size and shape of typical sweet potatoes. *TRANS. A.S.A.E.* 19: 678-682.
- Carrion, J., A. Torregrosa, E. Orti and E. Molto, 1998. First result of an automatic citrus sorting machine based on an unsupervised vision system. In: *Proceeding of Euro. Agr. Eng.* 1998. Olsa. pp: 98-F-019.
- Khojastapour, M., 1996. Design and fabrication method of potato sorting machine according to Iran conditions. M.Sc. thesis, Tehran University, Iran.

19. Marvin, J.P., G.M. Hyde and R.P. Cavalieri, 1987. Modeling potato tuber mass with tuber dimensions. *TRANS. A.S.A.E.* 30: 1154-1159.
20. Rashidi, M., R. Attarnejad, A. Tabatabaeefar and A. Keyhani, 2005a. Prediction of soil pressure-sinkage behavior using the finite element method. *Int. J. Agri. Biol.*, 7: 460-466.
21. Rashidi, M., A. Tabatabaeefar, R. Attarnejad and A. Keyhani, 2005b. Non-linear modeling of soil pressure-sinkage behavior applying the finite element method. In: *Proceedings of International Agricultural Engineering Conference*. 6-9 December 2005 Bangkok, Thailand.
22. Rashidi, M., A. Keyhani and A. Tabatabaeefar, 2006. Multiplate penetration tests to predict soil pressure-sinkage behavior under rectangular region. *Int. J. Agri. Biol.*, 1: 5-9.
23. Rashidi, M., A. Tabatabaeefar, R. Attarnejad and A. Keyhani, 2007. Non-linear modeling of pressure-sinkage behavior in soils using the finite element method. *J. Agric. Sci. Technol.*, 9: 1-13.
24. Rashidi, M. and M. Gholami, 2010. Prediction of soil sinkage by multiple loadings using the finite element methods. *Int. J. Agric. Biol.*, 12: 911-915.
25. Rashidi, M., M. Gholami, I. Ranjbar and S. Abbassi, 2010. Finite element modeling of soil sinkage by multiple loadings. *American-Eurasian J. Agric. & Environ. Sci.*, 8: 292-300.